



TRULUX LIGHTING SYSTEMS

TASK LIGHTING

DOWNLIGHTING

DECORATIVE LAMPS

CRESCENT  
ARCHITECTURAL LIGHTING

POWER SUPPLIES

## Features

- Wall mount sconce in new Graphite finish
- Low-VOC painted aluminum housing with polycarbonate lens
- 3000K color temperature with 90+ CRI
- cETLus Listed for wet locations
- 30,000 hours rated life

## Available Finishes



Graphite

## Listing / Ratings



## FRAMEWRX Crescent Wall Sconce

This contemporary sconce is graceful, yet powerful and long-lasting. It delivers 550 lumens without glare and provides a great option for residential, multi-family and commercial corridor and stair landing applications.

## Technical Information

|               |                              |
|---------------|------------------------------|
| Series        | SCO-CRESCENT                 |
| Input Voltage | 120-240V AC                  |
| CCT           | 3000K                        |
| CRI           | 90+                          |
| Wattage       | 10W                          |
| Lumens        | 550Lm                        |
| Beam Angle    | 120°                         |
| Dimmable      | N/A                          |
| Dimensions    | 4-5/16" W x 5-1/8" D x 18" H |
| Mounting      | Wall mount                   |
| Rating        | cETLus Listed (wet location) |
| Rated Life    | 30,000 hrs                   |

## Ordering Information

|                        |                      |
|------------------------|----------------------|
| <b>SCO-CRESCENT-GT</b> | Crescent Wall Sconce |
|------------------------|----------------------|